



Floor Heating - the easy way



Heating Mats

3mm heating mat available in 150w and 200w per metre. The cable is twin-conductor, insulated with Teflon, and both the earthing shield and cable are reinforced with Kevlar. The heating mats are fitted with 4 rows of double-sided adhesive tape.

200 W/m²

For sole source heating in conservatories and also for rooms where there is a high heat loss or the entire floor cannot be covered, eg. kitchens.

Size in m ²	Product code	Wattage	Width	Length
0.8	PRM 200 0080	160	0.5	1.60
1.6	PRM 200 0160	320	0.5	3.25
2.2	PRM 200 0220	440	0.5	4.40
3.1	PRM 200 0310	620	0.5	6.15
4.4	PRM 200 0440	880	0.5	8.65
5.5	PRM 200 0550	1100	0.5	10.90
6.1	PRM 200 0610	1220	0.5	12.25
7.0	PRM 200 0700	1400	0.5	14.00
7.9	PRM 200 0790	1580	0.5	15.85
8.9	PRM 200 0890	1789	0.5	17.40
9.6	PRM 200 0960	1920	0.5	19.20

150 W/m²

150 watt heating mats for comfort heating of floors, can be used as sole heating source in well insulated areas if output is above 130 w/m² of total room area.

Size in m ²	Product code	Wattage	Width	Length
1.0	PRM 150 0100	150	0.5	2.0
1.5	PRM 150 0150	225	0.5	3.05
2.0	PRM 150 0200	300	0.5	4.06
2.8	PRM 150 0280	416	0.5	5.50
3.3	PRM 150 0330	495	0.5	6.50
3.9	PRM 150 0390	585	0.5	7.70
4.7	PRM 150 0470	705	0.5	9.40
5.5	PRM 150 0550	819	0.5	10.90
6.0	PRM 150 0600	898	0.5	12.00
7.7	PRM 150 0770	1151	0.5	15.35
8.9	PRM 150 0890	1390	0.5	17.80
10.0	PRM 150 1000	1494	0.5	19.95



14A Manual Thermostat

- Easy to use with on/off switch and temperature dial
- Extendable floor sensor (100m)
- IP21
- 14A - 3200W

HT30



16A Programmable Thermostat

- Floor sensor, room sensor, floor and room sensor
- 7 day programmable thermostat
- IP21 rated
- Built in or surface mounted
- Sleep mode
- 16A - 3600W

HT10