



Extra Low Voltage Fan



Safety extra low voltage fan 100mm (4")

Suitable for mounting within the splash area of a shower or bath (where current regulations prevent the use of conventional fans) the 12v fan is a standard model manufactured with a 12v 50Hz shaded pole motor. The transformer and switching mechanism is mounted remotely either in the roof space or high on the ceiling next to the pull cord switch.

Bathroom fan

100mm 12v

Remote transformer

Standard

Pull cord

Timer

Timer +
pull cord override

Humidity control

Humidity control +
pull cord override

In-line Back Draught Shutters



Fitted in-line into the ducting to prevent unwanted back draughts.

100mm (4")

Gravity & Fixed Grills



Available in white, brown, grey or terracotta

100mm (4")

150mm (6")

PVC Flexi Ducting



Lightweight, reinforced with hardened steel wire spirally wound. ideal for extractor fans or tumble dryers.

100mm (4") ducting

3m length

10m length

150mm (6") ducting

5m length

Clamps

50mm - 110mm

60mm - 165mm

Gaffa Tape

Black

Silver

Centrifugal Fans



CF100 The CF100 centrifugal fan uses the latest technology to provide extremely powerful, yet very quiet and vibration free ventilation

- Ceiling/wall mounted
- Suitable for bathrooms and toilets
- 62m³/hr extract rate

CF100S Standard
CF100T Timer
CF100P Pullcord
CF100H Humidity



CF200 Designed to move air over long distances these units will give maximum performance even against pressures caused by long lengths of ducting and resistance by grills

- 110m³/hr extract rate
- 31 litres per second
- Double insulated

CF200S Standard
CF200T Timer
CF200P Pullcord
CF200H Humidity



CF400 The largest fan in the range, dynamically balanced, the CF400 unit is fitted with external rotor motors which incorporate ball bearings for a maintenance free life of over 40,000 hrs

- 230m³/hr extract rate
- 64 litres per second

CF400S Standard
CF400T Timer
CF400P Pullcord
CF400H Humidity