



Ceiling Globe Fitting



- Polycarbonate construction
- Opal glass diffuser
- BC GLS Lamp

60W
100W

Dimming Pull Switch



- Polycarbonate
- Pull action for on/off
- Prolonged pull for dimming
- 250w Incandescent load
- 175w Transformer load
- Not suitable for fluorescent lamps
- Includes white and chrome effect covers
- IP20 rated

DIM250

Halogen Floodlights



240v
150W
500W
1000

GU10/LV Ceiling Converters



- Pressed metal construction
- Converts traditional mains downlight and eyeball dimensions to modern GU10 or low voltage lighting
- Supplied with ceramic GU10 & LV lampholders
- IP20 rated


CR80BS Polished brass effect
CR80CR Polished chrome effect
CR80SN Brushed nickel effect
CR80WH White



Nema Socket Electronic Photocell Kit

- C/w wall fixing bracket
- Thermoplastic moulding
- 1500va or 5amp inductive load
- Switching at 70 lux
- IP44

Low Voltage Rope 5 Light Kit



- 5 light multi-directional light fixtures
- Matching 105va transformer with fitted 3 pin plug
- 10 metres of wire rope allowing up to 5 metre run
- Complete with all necessary fixings and accessories
- Requires 5 x 20w halogen lamps (supplied)
- Matt silver finish

Par 38 Garden Lighting



Ground Spike

Single
Twin

Surface Spot

Single
Twin

Plug in Ceiling Rose



Available unwired and pre-wired

- 4 terminals
- 6 Amp rated
- Pre-wired version comes with 2m of .75 4 core flex
- IP20

Unwired
Pre-wired
Lamps not included

Low Energy



Pendant

To be used with 4 pin plug in lamps only 13w and 18w versions

13w Pendant
18w Pendant
Lamps not included