



Columbus



The Columbus bulkhead fittings range is the round design that compliments the Mini-Max square product.

- HF Electronic or HPF switch start
- 3 hour maintained and auto test emergency versions available
- Factory fitted or self fit photocell kit available
- Semi recessing kit available
- Security screws available
- Black or white base
- IP65

FH20328R 28w 2D white/opal

Mini-Max



The Mini-Max range of energy efficient bulkhead fittings are manufactured with a polycarbonate base and diffuser.

Together with the proven feature of an extruded bi-seal hermetic gasket, the Mini-Max is at the forefront of vandal resistant IP65 technology.

Designed in partnership with the end user, Mini-Max, like many other Fern Howard fittings use the unique Time in a Box installation system. In addition a hinged gear tray and flying lead will also show significant savings of installation time and costs.

FH20-325-16 16w white/opal
 FH20-325-28 28w white/opal
 FH20-325-38 38w white/opal

Moonlight



The Moonlight security light offers exceptional value and outstanding peace of mind where safety and protection are the application requirements.

- Black base with opal diffuser
- Fitted photocell for dusk to dawn lighting
- IP34
- Non photocell option available
- Complete with 16w 2D lamp

FH790-B-OP 16w2D + Photocell
 FH795-B-OP 16w2D

Ice Breaker



Design features include an ultra-slim profile and snap fit diffuser, enabling Ice Breaker to be used for any IP44 application.

- Lowest profile ever only 75mm
- Snap fit diffuser
- All polycarbonate
- Complete with 28w2D lamp
- Rear besa cable entry
- IP44

FH20328R 28w 2D white/opal

Galileo



Galileo leads the Fern Howard range of architectural ceiling and wall mounted energy saving fittings.

- Shallow profile
- Wall or ceiling mounted
- Opal polycarbonate diffuser
- High power factor
- IP20
- Time in a Box

FH20-325-16 16w white/opal
 FH20-325-28 28w white/opal
 FH20-325-38 38w white/opal

Milan



The Fern Howard Milan range gives the specifier a unique opportunity to match architectural design with IP65 performance. The prismatic glass diffuser is surrounded by a polycarbonate bezel with a twist locking seal. The Milan is a flexible energy efficient CFL fitting for wall and ceiling mounting, also available with a translucent bases to give stunning back lighting effects.

Milan Coloured

