



Cast Fire Rated Downlights



F-Mark Thermal tested and approved for mounting on normally flammable surfaces to comply with F-marking requirements with 35w lamps. Also suitable for continuous use with 50w lamps.

Integrated intumescent material Incorporated in the downlight completely seals it in the event of a fire.

Maintains the ceiling fire barrier integrity In compliance with the building regulations approved document B, Fire Safety.

Maintains the ceiling acoustic properties In compliance with the building regulations approved document E, Resistance to the passage of sound.

Simple and versatile installation no different to a standard downlight, suitable for installation in ceiling materials up to 35mm thick.

Lamp Compatibility Designed for use with both Aluminium and Dichroic reflector lamps.

Fully Approved and Certified Complies with all relevant Safety, Acoustic and Fire regulations.

Common Features

- Integrated intumescent
- Material completely seals the downlight and cut out in the event of a fire
- Suitable for 30 and 60 minute fire rated ceilings
- Tested to BS476 Part 21
- 2 year guarantee
- 50w max
- Aluminium die-cast with lock ring
- Low and mains voltage

Fixed



- 75mm cut out
- Recess depth 139mm
- Lip depth 7mm

AU-DLL991*
12v MR16

AU-DLM981*
240v GU10

Adjustable



- 30 degree horizontal adjustment
- 85mm cut out
- Recess depth 144mm
- Lip depth 7mm

AU-DLL992*
12v MR16

AU-DLM982*
240v GU10

IP65



- IP65 jet proof showerlight
- 72mm cut out
- Recess depth 155mm
- Lip depth 10mm

AU-DLL993*
12v MR16

AU-DLM983*
240v GU10

*Add suffix W, PB, PC, SN, or SS to product number to denote finish required. Price excludes lamp and transformer where required.



Satin Nickel



Polished Brass



Polished Chrome



Satin Silver



White